


NUMBER OF PHASE	線相數	3
NUMBER OF POLES	極數	2
LINE TO LINE RESISTANCE	線線	4.9±10% ohms@20° C
LINE TO LINE INDUCTANCE	線線	0.65±20% mHENR/KHz
NOMINAL VOLTAGE	額定電壓	24 VDC
NOMINAL SPEED	空載轉速	30000±10% RPM
NO. LOAD CURRENT	空載電流	0.1 A
RATED TORQUE	每安培矩	4mN.m
RATED SPEED	每安轉速	25000 RPM
RATED CURRENT	每安電流	0.46A
PEAK TORQUE	每極轉矩	12% m
PEAK CURRENT	每極電流	1.4A
BACK EMF CONSTANT	反電勢係數	0.64 Vrms/ARPM
TORQUE CONSTANT	轉矩係數	8.6N.m/A
INSULATION CLASS	絕緣等級	B 130° C
DELECTRIC STRENG	介電強度	360VDC 1SER
INSULATION RESIST	絕緣電阻	1000Ohm @500VDC
ROTOR INERTIA	轉子轉動慣量	0.66g.cm ²
WEIGHT	重量	42g
OPERATION AMBIENT	使用環境	Ambient temperature:-20...+55° C, humidity Max. 85% (No condensation)
STORAGE AMBIENT	儲存環境	Ambient temperature:-10...+35° C, humidity Max. 85% (No condensation)



A	REV	ECO	NO.	DESCRIPTION	DATE	P/N.
				MATERIAL		
				COUNTER		
				CHECK		
				APPD.		
				SCALE		
				SHEET	OF	
				PULLING MOTOR		